

SOFASCO INC.

MTTF REPORT

MODEL NO	A17238V1HB	BEARING	BALL BEARING
VOLTAGE	115/60Hz V	CURRENT	0.29 A
SPEED	3350 RPM		
TESTED QTY	50 PCS	TEST HRS/EA	1405 HRS
TOTAL HRS	70250 HRS		
TEST TEMPERATURE	70 °C	TEST VOLTAGE	115/60Hz V

FAIL DEFINITION	CHECK POINT AT THE HOURS OF
1. FAN NOT RUNNING	<input checked="" type="checkbox"/> 0 HR <input checked="" type="checkbox"/> 1000 HR
2. SPEED OVER ± 15% OF SPEC.	<input checked="" type="checkbox"/> 72 HR <input checked="" type="checkbox"/> 1250 HR
3. CURRENT OVER OF SPEC. (MAX)	<input checked="" type="checkbox"/> 300 HR <input type="checkbox"/> 1500 HR
4. NOISE OVER +3dB OF SPEC. (MAX)	<input checked="" type="checkbox"/> 600 HR

FAIL TIME RECORD(HRS)											
1ST		2ND		3RD		4TH		5TH		6TH	
7TH		8TH		9TH		10TH		11TH		12TH	

TEST RESULT																			
<p>CONFIDENCE LEVEL= 90%</p> <p>ACCELERATION FACTOR= A temp x A volt</p> <p>$\{e^{[(\Delta H/K) * [(1/Temp\ 1)-(1/Temp\ 2)]]}\} \times [(V\ h.s./V\ l.s.)^n]$</p>																			
<p>MTTF(HRS)</p> <p style="text-align: center;">TEMP(CENTIGRADE) °C</p>																			
<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th>TEMP</th> <th>30</th> <th>40</th> <th>50</th> <th>60</th> <th>70</th> </tr> </thead> <tbody> <tr> <td>MTTF</td> <td>402210</td> <td>278701</td> <td>197557</td> <td>142960</td> <td>105424</td> </tr> <tr> <td>L10</td> <td>42337</td> <td>29336</td> <td>20795</td> <td>15048</td> <td>11097</td> </tr> </tbody> </table>	TEMP	30	40	50	60	70	MTTF	402210	278701	197557	142960	105424	L10	42337	29336	20795	15048	11097	
TEMP	30	40	50	60	70														
MTTF	402210	278701	197557	142960	105424														
L10	42337	29336	20795	15048	11097														

APPROVED BY	CHECKED BY	PREPARED BY
MICHAEL WANG	LILY TSAI	LUCY KUO