

DB5015 Series

51X51X15mm(2.0"X2.0"X0.59")



HOUSING	Thermoplastic PBT, UL94V-0
IMPELLER	Thermoplastic PBT, UL94V-0
BEARING	Ball
OPERATING TEMPERATURE	-30 °C to +75 °C
INSULATION RESISTANCE	10 meg Ohms Min.@500 VDC (Between Frame and Terminal)
DIELECTRIC STRENGTH	5 mA Max. at 500 VAC 60Hz for 1 minute (Between Frame and Terminal)
WEIGHT	28g

MODEL NO.	RATED VOLTAGE (V)	RATED CURRENT (A)	INPUT POWER (W)	SPEED (RPM)	MAX. AIR PRESSURE		Maximum Air Flow		NOISE dB(A) @1M
					inchH ₂ O	mmH ₂ O	CFM	m ³ /min	
DB5015V5M	5	0.31	1.55	5500	0.52	13.4	4.1	0.11	41
DB5015V5L	5	0.17	0.85	4500	0.35	8.9	3.3	0.09	36
DB5015V12H	12	0.21	2.52	6500	0.76	19.5	4.8	0.13	45
DB5015V12M	12	0.12	1.5	5500	0.52	13.4	4.1	0.11	41
DB5015V12L	12	0.08	0.96	4500	0.35	8.9	3.3	0.09	36
DB5015V24H	24	0.13	3.12	6500	0.76	19.5	4.8	0.13	45
DB5015V24M	24	0.09	2.16	5500	0.52	13.4	4.1	0.11	41
DB5015V24L	24	0.06	1.56	4500	0.35	8.9	3.3	0.09	36

AIR FLOW →

